



DRG-SERIES

DEMOLITION & SORTING GRABS



Heavy duty rotation motor(s) with shock protection.

(Two rotation motors from DRG 25 standard, DRG 17-22 optional)

Load safety valve intergrated in the distributor.

Filters in rotation circuit.

Robust end stops.

Double roller ring (from DRG-28).

Hydraulic cylinder end damping.

Pivots sealed grease in debris out.

Divided bolt on blades.



Type	DRG-14	DRG-15	DRG-17	DRG-19	DRG-22	DRG-25	DRG-27	DRG-28	DRG-36	DRG-45	DRG-65
Carrier weight*	10-18 ton	12-20 ton	12-24 ton	13-25 ton	15-30 ton	18-28 ton	20-30 ton	20-40 ton	25-50 ton	35-60 ton	50-80 ton
Weight (ca.)**	855 kg	895 kg	1025 kg	1115 kg	1315 kg	1450 kg***	1495 kg***	1790 kg	2010 kg	2390 kg	4165 kg
Capacity	340 L	415 L	365 L	480 L	570 L	650 L	760 L	825 L	960 L	1075 L	1660 L
Closing force	43 kN	43 kN	50 kN	48 kN	56 kN	60 kN	60 kN	70 kN	80 kN	80 kN	140 kN

Dimensions											
Opening	1730 mm	1730 mm	1724 mm	1864 mm	1967 mm	2050 mm	2050 mm	2193 mm	2325 mm	2325 mm	2700 mm
Width	750 mm	900 mm	850 mm	1000 mm	1000 mm	1000 mm	1200 mm	1100 mm	1250 mm	1400 mm	1500 mm
Height	1217 mm	1217 mm	1344 mm	1377 mm	1458 mm	1440 mm***	1440 mm***	1536 mm	1629 mm	1733 mm	2217 mm

Hydraulic											
Opening/Closing P _{max}	350 bar	350 bar	350 bar	350 bar	350 bar	350 bar	350 bar	350 bar	350 bar	350 bar	350 bar
Flow	80 l/min	80 l/min	100 l/min	100 l/min	100 l/min	100 l/min	100 l/min	120 l/min	120 l/min	120 l/min	200 l/min
Rotation P _{max}	140 bar	140 bar	140 bar	140 bar	140 bar	140 bar	140 bar	140 bar	140 bar	140 bar	140 bar
Flow	40 l/min	40 l/min	40 l/min	40 l/min	40 l/min	40-60 l/min	40-60 l/min	40-60 l/min	40-60 l/min	40-60 l/min	40-60 l/min

DRG-04-13-EN * Depending on capacity of carrier ** Weight excluding bracket ***Inclusive CW4 (integrated)

Subject to change without notice.

Trendsetter in Demolition and Recycling Equipment

DEMAREC
Demolition and Recycling Equipment BV
 Den Hoek 10 • 5845 EL St. Anthonis (NL)
 Tel. +31(0)485 442300 • E-mail: info@demarec.com

demarec.com